

- Hinged terminal covers
- Can be mounted directly onto panel or DIN rail mounted
- Supplied with DIN Rail mounting bracket for horizontal or vertical mounting



CP62/WS-5/5

CP62/30-50/5


CP86/60-500/5

CP140/100-1200/5

Part Number	Description	VA	Class
CURRENT TRANSFORMERS - PRIMARY WOUND			
CP62/WS-5/5	5/5A	1.5	3.0
CP62/WS-10/5	10/5A	1.5	3.0
CP62/WS-15/5	15/5A	1.5	1.0
CP62/WS-20/5	20/5A	2.5	1.0
CP62/WS-25/5	25/5A	2.5	1.0
CURRENT TRANSFORMERS - 14mm I.D RING TYPE			
CP45/14-30/5	30/5A	2.5	1.0
CP45/14-40/5	40/5A	2.5	1.0
CURRENT TRANSFORMERS - 30mm I.D RING TYPE			
CP62/30-50/5	50/5A	2.5	1.0
CP62/30-60/5	60/5A	2.5	1.0
CP62/30-75/5	75/5A	2.5	1.0
CP62/30-100/5	100/5A	2.5	1.0
CP62/30-125/5	125/5A	5	1.0
CP62/30-150/5	150/5A	5	1.0
CP62/30-200/5	200/5A	5	1.0
CP62/30-250/5	250/5A	5	1.0
CURRENT TRANSFORMERS - 40mm I.D RING TYPE			
CP62/40-150/5	150/5A	5	1.0
CP62/40-200/5	200/5A	5	1.0
CP62/40-250/5	250/5A	5	1.0
CP62/40-300/5	300/5A	5	1.0
CURRENT TRANSFORMERS - 50mm I.D RING TYPE			
CP/74/50-300/5	300/5A	5	1.0
CP/74/50-400/5	400/5A	5	1.0
CURRENT TRANSFORMERS - 60mm I.D RING TYPE			
CP/86/60-500/5	500/5A	5	1.0
CP/86/60-600/5	600/5A	5	1.0
CP/86/60-750/5	750/5A	5	1.0
CP/86/60-800/5	800/5A	5	1.0
CP/86/60-1000/5	1000/5A	5	1.0
CP/86/60-1250/5	1250/5A	5	1.0
CURRENT TRANSFORMERS - 80mm I.D RING TYPE			
CP104/80-750/5	750/5A	15	1.0
CP104/80-800/5	800/5A	15	1.0
CP104/80-1000/5	1000/5A	15	1.0
CP104/80-1200/5	1200/5A	15	1.0
CP104/80-2000/5	2000/5A	15	1.0
CURRENT TRANSFORMERS - 100mm I.D RING TYPE			
CP140/100-1200/5	1200/5A	15	1.0
CP140/100-1500/5	1500/5A	15	1.0
CP140/100-1600/5	1600/5A	15	1.0
CP140/100-2000/5	2000/5A	15	1.0
CP140/100-2500/5	2500/5A	15	1.0
CP140/100-3000/5	3000/5A	15	1.0

- Moving Iron or Shunt Connected Moving Coil
- Standard over scale 100%


AMMETERS - (Direct Reading) Moving Iron - STANDARD OVER SCALE 100%



AMI-48- * A	5, 10, 15, 20, 30, Amp	Size: 48 x 48 mm
AMI-72- * A	5, 10, 15, 20, 30, 40, 50 Amp	Size: 72 x 72 mm
AMI-96- * A	5, 10, 15, 20, 30, 40, 50 Amp	Size: 96 x 96 mm

● ○ ● ● Colour bezels available: Red, White, Black and Blue. * Please specify.

AMMETERS - (CT Operated 5A) Moving Iron - STANDARD OVER SCALE 100%




48- * /5	CT Operated AC Ammeter	48 x 48 mm
72- * /5	CT Operated AC Ammeter	72 x 72 mm
96- * /5	CT Operated AC Ammeter	96 x 96 mm

*Scales available from: 30/5 up to 3000/5

● ○ ● ● Colour bezels available: Red, White, Black and Blue. * Please specify.

DC AMMETER (SHUNT CONNECTED) MOVING COIL




CP72- * /A	50mV DC Ammeter	72 x 72 mm
-------------------	-----------------	------------

Available in 5, 10, 20, 30, 40, 50, 100, 150 & 200A DC (* Please specify when ordering)

● ○ ● ● Colour bezels available: Red, White, Black and Blue. * Please specify.

****EXCLUDES SHUNT**

AMMETER SWITCH 1 POLE - FOR 3CT OPERATION



Part Number	Description	kW AC3	Current Rating
C11-22-11	1P Ammeter Switch	2,7kW	10Amps

AMMETER SWITCH 3 POLE - DIRECT READING

Part Number	Description	kW AC3	Current Rating
C11-14-11	3P Ammeter Switch	2,7kW	10Amps



AC VOLTMETERS MOVING IRON

VMI-48 * /V	AC Voltmeter	48 x 48mm
VMI-72 * /V	AC Voltmeter	72 x 72mm
VMI-96 * /V	AC Voltmeter	96 x 96mm

Available in the following voltages : 300, 400, 500 & 600 VAC * Please specify.

● ○ ● ● Colour bezels available: Red, White, Black and Blue. * Please specify.



DC VOLTMETERS MOVING COIL

CP72 - * /V	DC Voltmeter 72 x 72mm
--------------------	------------------------

Available from and up to 15, 30, 50, 60, 100, 150, & 200VDC *Please specify.



RUNNING HOUR METERS

BZ142 - *	Running Hour Meter	48x 48mm or 72 x 72mm
------------------	--------------------	-----------------------

*Available in the following voltages - 12VAC, 48VAC, 110VAC, 230VAC

BZ142 - *	Running Hour Meter - 12VDC, 24VDC, 400VAC	48mm ² or 72mm ²
------------------	--	--

*PLEASE SPECIFY VOLTAGE & CURRENT RATING



MAXIMUM DEMAND AMMETERS - CT OPERATED - 15 MIN/5A

MD-72 - * /5	2 Needle (No Instantaneous)	72 x 72mm
MD-96 - * /5	2 Needle (No Instantaneous)	96 x 96mm



MAXIMUM DEMAND AMMETERS + INSTANTANEOUS - CT OPERATED - 15 MIN/5A

MDI-72 - * /5	3 Needle with Instantaneous	72 x 72mm
MDI-96 - * /5	3 Needle with Instantaneous	96 x 96mm

Available 100/5 up to 3000/5 *Please specify.

● ○ ● ● Colour bezels available: Red, White, Black and Blue. * Please specify.



FREQUENCY METER - POINTER TYPE

FA72 -P- *	45 - 55Hz Pointer Type Frequency	72 x 72mm
-------------------	----------------------------------	-----------

FA96 -P- *	45- 55Hz Pointer Type Frequency	96 x 96mm
-------------------	---------------------------------	-----------



VOLTMETER SWITCHES

VOLTMETER SWITCH 3 PHASE - (OFF-RW-WB-BR)

C11-16-11	3P Voltmeter Switch	2,7kW	10Amps
------------------	---------------------	-------	--------

VOLTMETER SWITCH 3 PHASE TO NEUTRAL - (OFF-RN-WN-BN)


C11-15-11	3P Voltmeter Switch	2,7kW	10Amps
------------------	---------------------	-------	--------

VOLTMETER SWITCH 7 POSITION PHASE TO PHASE & PHASE TO NEUTRAL + OFF

C11-18-11	3P Voltmeter Switch	2,7kW	10Amps
------------------	---------------------	-------	--------

22MM AC DIGITAL AMMETERS WITH CURRENT TRANSFORMER

NEW!




AD22-22AM-
AC AMMETER WITH
100A CURRENT
TRANSFORMER
24VAC - 400VAC ONLY
**Please specify colour*

W	○
G	●
R	●
Y	●
B	●

22MM AC & DC DIGITAL VOLTMETERS

NEW!



AD22-22VM-AC-
AC VOLTMETER
20VAC - 500VAC ONLY
**Please specify colour*

W	○
G	●
R	●
Y	●
B	●

NEW!



AD22-22VM-DC-
DC VOLTMETER
5VDC - 60VDC ONLY
**Please specify colour.*

G	●
R	●

22MM AC DIGITAL HERTZ METERS

NEW!



AD22-22HZ-
AC HERTZ METER
24VAC - 525VAC ONLY
**Please specify colour*

W	○
G	●
R	●
Y	●
B	●

22MM TEMPERATURE METERS

NEW!




AD22-22TM-
TEMPERATURE
50VAC - 380VAC
0°C - 199°C ONLY
**Please specify colour*

W	○
G	●
R	●
Y	●
B	●

1M EXTENSION CORD

NEW!



AD22-1M-C
1 METER EXTENSION CORD FOR THE
AD22-22 RANGE AMMETER WITH
CURRENT TRANSFORMER